

VEDAFEU SFR[®] SEALANT

“ *The perfect solution
 for small gaps* ”



**TESTED
 CERTIFIED**

FIRESTOP
 EI 120

HANDLING
 EASY

JOINT WIDTHS
 5 to 10 mm

OFFICIAL CLASSIFICATION

Classification report n° EFR-21-L-001690

EI 120 - H - X - B - W 5 to 10


VEDAFEU SFR[®] PROPERTIES

| | |
|-------------------------------|---|
| Type of sealant | Intumescent (acrylic sealant) |
| Colour | White |
| Minimum depth of application | 10mm |
| Minimum operating temperature | 5 °C |
| Storage temperature | 5 to 25 °C |
| Shelf life | 18 months (when stored in original unopened packaging in a fresh and dry place) |
| Packaging | 310ml cartridge / 600ml bag |

Installation instructions for joint widths from 5 to 10mm*



If necessary, remove formwork material such as polystyrene, honeycomb cardboard, etc.



Apply protective tape on the edges of the joint.
 Apply Vedacol[®] adhesive on the internal edges of the joint.



Introduce the backer rod to a minimum depth of 10mm.



Apply the VEDAFEU SFR[®] sealant, then smooth off the surface and remove the tape.



VEDAFEU SFR sealant[®] after installation.

Surfaces must be clean, dry, free of dust, grease or other products that could prevent the sealant from adhering. The cleaning of the supports must be carried out with appropriate products, always following the recommendations of the suppliers. In the case of unfamiliar surfaces, it is recommended to proceed with a test beforehand in order to determine the necessity of using a primer.

*Complete installation method available upon request.

© All rights reserved - Non contractual drawings - 10/2021

