

VEDAFEU SFR[®] SEALANT

“ *The perfect solution
 for small gaps* ”



**TESTED
 CERTIFIED**

FIRESTOP
EI 120

HANDLING
EASY

JOINT WIDTHS
5 to 10mm

OFFICIAL CLASSIFICATION

Classification report n° EFR-21-L-001690

EI 120 - H - X - B - W 5 to 10


VEDAFEU SFR[®] PROPERTIES

Type of sealant	Intumescent (acrylic sealant)
Colour	White
Minimum depth of application	10mm
Minimum operating temperature	5 °C
Storage temperature	5 to 25 °C
Shelf life	18 months (when stored in original unopened packaging in a fresh and dry place)
Packaging	310ml cartridge / 600ml bag

Installation instructions for joint widths from 5 to 10mm*



If necessary, remove formwork material such as polystyrene, honeycomb cardboard, etc.



Apply protective tape on the edges of the joint.
 Apply Vedacolle[®] adhesive on the internal edges of the joint.



Introduce the backer rod to a minimum depth of 10mm.



Apply the VEDAFEU SFR[®] sealant, then smooth off the surface and remove the tape.



VEDAFEU SFR sealant[®] after installation.

Surfaces must be clean, dry, free of dust, grease or other products that could prevent the sealant from adhering. The cleaning of the supports must be carried out with appropriate products, always following the recommendations of the suppliers. In the case of unfamiliar surfaces, it is recommended to proceed with a test beforehand in order to determine the necessity of using a primer.

*Complete installation method available upon request.

