




VEDAFEU N20[©] Blankets according to initial joint width

Initial joint width [mm]	100	150	200	250	300
Reference VEDAFEU N20 [©]	N20-100	N20-150	N20-200	N20-250	N20-300
Conditioning [m]			5		

Installation instructions for joint widths from 100 to 300mm*

If necessary, remove formwork material such as polystyrene, honeycomb cardboard, etc. Remove dust, using a brush or a broom.



Apply the VEDACOLLE^{©**} adhesive on 80mm depth on both sides of the joint. Use approx 1kg/ml of VEDACOLLE^{©**}.



Put VEDAFEU linking material around the junction and seal it with some VEDACOLLE®** adhesive.



Insert the blanket VEDAFEU N20° into the joint before the adhesive dries.



VEDAFEU N20[©] Blanket is installed.

Efectis

To splice two lengths of blanket, apply adhesive on the extremity of both blankets before compressing them together.



*Brief installation instructions. Complete installation method available upon request. **When applying the VEDACOLLE[®] adhesive, supports must be dry and clean. In case of potential exposure to water and/or weather conditions, the system must be protected by a VED'EPDM® membrane.

For installation accessories, approved concrete supports and thicknesses, please refer to the concerned classification report. The guantities needed for the VEDAFEU installation are indicated in the classification report and in our installation method. Installation video and method available upon request.

VEDAFEU N20[©] PROPERTIES

VEDAFEU N20[®] firestop blankets COMPRESSIBILITY tests

Reference VEDAFEU N20 [©]	Compressibility	
N20-100	87%	L∳
N20-200	92%	
N20-300	89%	

Results of test report n° DSSF 23-24041 dated 22/02/2024 (available upon request).

VEDAFEU N20[©] MOVEMENT CYCLES tests

Reference VEDAFEU N20 [©]	VEDAFEU N20-100	VEDAFEU N20-200	VEDAFEU N20-300
Initial joint width (mm)	100	200	300
Maximum gap (mm)	150	300	450
Minimum gap (mm)	50	100	150
Number of cycles		500	

Results of test report n° DSSF 20-00179 dated 10/05/2022 (available upon request).